

- ① PROTECT UTILITY POLE. COORDINATE WITH UTILITY COMPANY FOR STABILIZATION.
 - ② PROTECT TREES - GROUND DISTURBING ACTIVITY MUST NOT OCCUR WITHIN 6 FEET OF TREE BASE. NOTIFY CITY IF ROOTS 3" OR GREATER ENCOUNTERED - DO NOT CUT.
- ASPHALT SURFACE

SHIELDED RUBBER COUPLING USED TO JOIN PVC AND VCP PIPE. CONCRETE COLLAR ENCOMPASSED COUPLING.

CONNECT TO EXISTING SANITARY SEWER, (15-INCH VCP) CONNECTION SHALL BE MADE WITH CONCRETE COLLAR PER CITY STANDARDS

PROTECT 2" WATER MAIN IN EXCAVATION

ACTUAL EXTENTS OF ASPHALT SURFACE. SIDEWALK REMOVED AND REPLACED WITH ASPHALT

RECONNECT EXISTING SEWER LATERAL 2+03.70 (W). VERIFY LOCATION
6" VCP LATERAL

RECONNECT EXISTING SEWER LATERAL 2+50.59 (W). VERIFY LOCATION
6" VCP LATERAL

SHIELDED RUBBER COUPLING USED TO JOIN PVC AND VCP PIPE. CONCRETE COLLAR ENCOMPASSED COUPLING.

CONNECT TO EXISTING SANITARY SEWER, (18-INCH VCP) CONNECTION SHALL BE MADE WITH CONCRETE COLLAR PER CITY STANDARDS

4" C.I. LATERAL
RECONNECT EXISTING SEWER LATERAL 2+49.50 (E). VERIFY LOCATION

(APPROXIMATE LOCATION) 2-INCH GAS MAIN TO BE CAPPED AND ABANDONED TO THE SOUTH BY SWL&P. REFER TO SPECIAL PROVISIONS FOR DETAILS.

PROPOSED STRUCTURE TABLE			
STRUCTURE	DETAILS	TYPE/COVER	LOCATION
PSMH1	RIM = 651.06 INV IN (S) = 639.38 (FIELD VERIFY) INV OUT (N) = 639.25 (FIELD VERIFY)	4-FT DIA MH/ SOLID COVER	1+62.07 0.0

